


Sicht auf die Stiftseite

Pin	Belegung	Farbe
1	Test	naturfarben
2	0V Sensor	Brücke auf Pin 9
3	SCL*	blau
4	RI-	grau
5	A2-	rot
6	A1-	gelb
7	V+ Sensor	Brücke auf Pin 8
8	V+	schwarz
9	0V	weiß
10	S1	orange
11	S2	violett
12	RI+	braun
13	A2+	rosa
14	A1+	grün
15	nc	--
Gehäuse	Schirm	Schirm

\* Eingang, darf Kundenseitig nicht belegt werden



View on pins

Pin	Signal	Color
1	Test	ecru
2	0V sensor	connected to pin 9
3	SCL*	blue
4	RI-	gray
5	A2-	red
6	A1-	yellow
7	V+ sensor	connected to pin 8
8	V+	black
9	0V	white
10	S1	orange
11	S2	violet
12	RI+	brown
13	A2+	pink
14	A1+	green
15	nc	--
housing	shield	shield

\* input, must not be used by customer

connection layout ~1Vss YT		Pin Layout		Change No. C015019-5	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)					
<b>RSF Elektronik</b> www.rsf.at		Serie	Version	Revision	Sheet
		<b>D1128788 - 00 - C - 01</b>			Page 1/1
Document No					