


Sicht auf die Stiftseite

Pin	Belegung	Farbe
1	A1-	gelb
2	A2-	rot
3	RI+	braun
4	V+	schwarz
5	V+ Sensor	Brücke auf Pin 4
6	Test	naturfarben
7	S2	violett
8	S1	orange
9	A1+	grün
10	A2+	rosa
11	RI-	grau
12	0V	weiß
13	0V Sensor	Brücke auf Pin 12
14	SCL*	blau
15	nc	--
Gehäuse	Schirm	Schirm

* Eingang, darf Kundenseitig nicht belegt werden



View on pins

Pin	Signal	Color
1	A1-	yellow
2	A2-	red
3	RI+	brown
4	V+	black
5	V+ sensor	connected to pin 4
6	Test	ecru
7	S2	violet
8	S1	orange
9	A1+	green
10	A2+	pink
11	RI-	gray
12	0V	white
13	0V sensor	connected to pin 12
14	SCL*	blue
15	nc	--
housing	shield	shield

* input, must not be used by customer

connection layout ~1Vss 6s		Pin Layout		Change No. C092004-05	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)					
RSF Elektronik www.rsf.at		Nicht-Serie	Version	Revision	Sheet
		D1286500 - 00 - A - 01			Page 1/1
Document No					