


Sicht auf die Stiftseite



View on pins

Pin	Belegung	Farbe
A	Schirm	Schirm
B	0V	weiß
C	T1	grün
D	T1 invers	gelb
E	T2	rosa
F	0V	Brücke auf Pin B
G	RI	braun
H	RI invers	grau
J	0V	Brücke auf Pin B
K	V+	schwarz
L	T2 invers	rot
M	V+	Brücke auf Pin K
Gehäuse	Schirm	Schirm
-	S1 *	orange
-	S2 *	violett

* ausgeführt als offene Litze, am Stecker nicht belegt

Pin	Signal	Color
A	shield	shield
B	0V	white
C	T1	green
D	T1 inverse	yellow
E	T2	pink
F	0V	connected to pin B
G	RI	brown
H	RI inverse	gray
J	0V	connected to pin B
K	V+	black
L	T2 inverse	red
M	V+	connected to pin K
housing	shield	shield
-	S1 *	orange
-	S2 *	violet

* performed as an open wire, on connector not connected

connection layout TTL Pb		Pin Layout		Change No: C195321-06	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)					
RSF Elektronik		Serie	Version	Revision	Sheet
www.rsf.at		D1509711 - 00 - A - 01			Page 1/1
Document No					