


Sicht auf die Stiftseite

Pin	Belegung	Farbe
1	Test	naturfarben
2	0V Sensor	Brücke auf Pin 9
3	US invers	blau
4	RI invers	grau
5	T2 invers	rot
6	T1 invers	gelb
7	V+ Sensor	Brücke auf Pin 8
8	V+	schwarz
9	0V	weiß
10	nc	--
11	nc	--
12	RI	braun
13	T2	rosa
14	T1	grün
15	nc	--
Gehäuse	Schirm	Schirm



View on pins

Pin	Signal	Color
1	Test	ecru
2	0V sensor	connected to pin 9
3	US inverse	blue
4	RI inverse	gray
5	T2 inverse	red
6	T1 inverse	yellow
7	V+ sensor	connected to pin 8
8	V+	black
9	0V	white
10	nc	--
11	nc	--
12	RI	brown
13	T2	pink
14	T1	green
15	nc	--
housing	shield	shield

connection layout TTL ZD		Pin Layout		Change No. C022391-5	
<small>The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)</small>					
RSF Elektronik		Serie	Version	Revision	Sheet
www.rsfs.at		D1143258 - 00 - C - 01			Page 1/1
<small>Document No</small>					