


Sicht auf die Stiftseite



View on pins

Pin	Belegung	Farbe
A	nc	-
B	0V	weiß
C	T1	grün
D	T1 invers	gelb
E	T2	rosa
F	S1	orange
G	RI	braun
H	RI invers	grau
J	S2	violett
K	V+	schwarz
L	T2 invers	rot
M	US invers	blau
Gehäuse	Schirm	Schirm

Pin	Signal	Color
A	nc	-
B	0V	white
C	T1	green
D	T1 inverse	yellow
E	T2	pink
F	S1	orange
G	RI	brown
H	RI inverse	gray
J	S2	violett
K	V+	black
L	T2 inverse	red
M	US inverse	blue
housing	shield	shield

connection layout TTL 1h	Pin Layout	Change No. C030490-93														
<small>The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)</small>																
<b>RSF Elektronik</b> www.rsf.at	<table border="1"> <tr> <td>Serie</td> <td>Version</td> <td>Revision</td> <td>Sheet</td> <td>Page</td> </tr> <tr> <td colspan="4"><b>D1222516 - 00 - B - 01</b></td> <td>1/1</td> </tr> <tr> <td colspan="5">Document No</td> </tr> </table>	Serie	Version	Revision	Sheet	Page	<b>D1222516 - 00 - B - 01</b>				1/1	Document No				
Serie	Version	Revision	Sheet	Page												
<b>D1222516 - 00 - B - 01</b>				1/1												
Document No																