


Sicht auf die Stiftseite



View on pins

Pin	Belegung	Farbe
1	A1+	grün
2	A1-	gelb
3	A2+	rosa
4	A2-	rot
5	RI+	braun
6	RI-	grau
7	V+	schwarz
8	0V	weiß
9	nc	--
10	nc	--
11	nc	--
12	V+ Sensor	Brücke auf Pin 7
13	0V Sensor	Brücke auf Pin 8
14	SCL *	blau
15	Test	naturfarben
Gehäuse	Schirm	Schirm

* Eingang, darf Kundenseitig nicht belegt werden

Pin	Signal	Color
1	A1+	green
2	A1-	yellow
3	A2+	pink
4	A2-	red
5	RI+	brown
6	RI-	gray
7	V+	black
8	0V	white
9	nc	--
10	nc	--
11	nc	--
12	V+ sensor	connected to pin 7
13	0V sensor	connected to pin 8
14	SCL *	blue
15	test	ecru
housing	shield	shield

* input, must not be used by customer

connection layout ~1Vss 4g	Pin Layout	Change No. C065459-72
<small>The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)</small>		
RSF Elektronik www.rsf.at	Serie	Version
	D1250335 - 00 - B - 01	
	Revision	Sheet
	Page	1/1
	Document No	