


Sicht auf die Stiftseite

Pin	Belegung	Farbe
1	V+	schwarz
2	T1 invers	gelb
3	T2	rosa
4	T2 invers	rot
5	Belegt*	violett
6	US invers	blau
7	RI	braun
8	RI invers	grau
9	Test	naturfarben
10	T1	grün
11	Belegt*	orange
12	0V	weiß
Gehäuse	Schirm	Schirm

* Eingang, darf Kundenseitig nicht belegt werden



View on pins

Pin	Signal	Color
1	V+	black
2	T1 inverse	yellow
3	T2	pink
4	T2 inverse	red
5	<u>occupied*</u>	violet
6	US inverse	blue
7	RI	brown
8	RI inverse	gray
9	Test	ecru
10	T1	green
11	<u>occupied*</u>	orange
12	0V	white
housing	shield	shield

* input, must not be used by customer

connection layout TTL 6f		Pin Layout		Change No. C089505-05	
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)					
RSF Elektronik		Serie	Version	Revision	Sheet
www.rsف.at		D1280038 - 00 - A - 01			Page 1/1
Document No					